

Overview of the sampling results at producers and warehouse operators of AGQM in 2022

Parameter	Unit	DIN EN 14214		95 Quantile* 2022
		min.	max.	
Ester Content	% (m/m)	96.5	-	97.0
Sulphur Content	mg/kg	-	10	7.5
Water Content (Producers)	% (m/m)	-	0,050 0,027**	0.024
Total Contamination	mg/kg	-	24 20**	14
Oxidation Stability (at 110 °C)	h	8.0	-	8.6
Acid Number	mg KOH/g	-	0.50	0.45
Iodine Number	g Iodine / 100 g	-	120	113
Linolenic Acid Methyl Ester	% (m/m)	-	12.0	9.8
Free Glycerol	% (m/m)	-	0.02	0.016
Monoglyceride Content	% (m/m)	-	0.70	0.61
Diglyceride Content	% (m/m)	-	0.20	0.17
Triglyceride Content	% (m/m)	-	0.20	0.09
Total Glycerol Content	% (m/m)	-	0.25	0.19
Alkali Metal Content (Na+K)	mg/kg	-	5.0	1.7
Alkaline Earth Metal Content (Ca+Mg)	mg/kg	-	5.0	0.1
Phosphorus Content	mg/kg	-	4.0	0.8

* The 95 Quantile describes the value below or above which 95% of all results are laying (excluding products with limit violations and products for which special limit values apply).

** Limits requested by AGQM.



Parameter	Unit	DIN EN 14214		95 Quantile* 2022
			max.	
Cloudpoint (blend component for Diesel)	°C	16.11. to 29.02	-3	-4
		15.04. to 30.09.	5	0
		01.10. to 15.11	0	-3
CFPP (blend component for Diesel)	°C	16.11. to 29.02	-10	-10
		15.04. to 30.09.	0	-4
		01.10. to 15.11	-5	-8

* The 95 Quantile describes the value below or above which 95% of all results are laying (excluding products with limit violations and products for which special limit values apply).

